



NOTES:

The figure 101 can not be used on a pipe or flange with an inside diameter less than the "E" dimension.

API Standard 609

VALVE DIMENSIONS

Size	A	B	C	D	E	F	G	H	K	Keyway	Weight	Top Plate Drilling		
												Bolt Circle	No. of Holes	Hole Dia.
2"	2 1/8	4 1/8	5 1/2	1 5/8	1 11/16	4	1 1/4	9/16	3/8	-	6	3 1/4	4	7/16
2.5"	2 9/16	4 7/8	6	1 3/4	2 3/16	4	1 1/4	9/16	3/8	-	8	3 1/4	4	7/16
3"	3 1/8	5 3/8	6 1/4	1 3/4	2 7/8	4	1 1/4	9/16	3/8	-	9	3 1/4	4	7/16
4"	4 1/8	6 7/8	7	2	3 7/8	4	1 1/4	5/8	7/16	-	13	3 1/4	4	7/16
5"	5 3/16	7 5/8	7 1/2	2 1/8	5	4	1 1/4	5/8	7/16	-	15	3 1/4	4	7/16
6"	6 1/8	8 3/4	8	2 1/8	6	4	1 1/4	5/8	7/16	-	19	3 1/4	4	7/16
8"	8 1/8	11	9 1/2	2 1/2	8	6	1 1/4	3/4	1/2	-	31	5	4	9/16
10"	10 1/8	13 3/8	10 3/4	2 1/2	10 1/16	6	1 1/4	7/8	5/8	-	47	5	4	9/16
12"	12 3/32	16 1/8	12 1/4	3	11 15/16	6	2	1 1/8	-	1/4x1/8	88	5	4	9/16

Item No.	Name	No. Req'd	Material	Remarks
1	Lugged Body	1		
2	Disc	1		
3	Stem	1		
4	Seat	1		
5	Bushing	1		
6	Screw	2		
7	"O-Ring"	2		
8	Seal	1		
9	Key	1		

SUBASSEMBLY PART NUMBER				
Trim	Part	Size	Figure No.	Style
ABZ MANUFACTURING, Inc. 2"-12" Figure 101 Valve Standard Wafer Pattern				
BODY: Flangeless w/360° Top Plate DISC: Standard STEM: One Piece w/Flats/Keyway SEAT: Elastomer				
BY	DATE	DESCRIPTION		
REVISIONS			DRAWING NO.	ED 101